

Marine scale

UNI SYSTEM
SWEDEN
WEIGHING SOLUTIONS



www.marinescale.com

FEATURES

Capacities 3-150 kg

Platform sizes 286x345 mm
350x350 mm
348x415 mm
500x600 mm

Measurement speed
0,4 Seconds

Powered by 230VAC
12-29VDC
12V 7Ah battery

Power consumption
25mA at 230VAC
200mA at 24VDC

Temperature range
-10°C to + 40°C

Protection IP67

Stainless steel SAE/AISI 316
EN/DIN 1.4401

Compensates automatically for

- Gravity: Worldwide
- Motion: Up to 3 m/s²
- Tilt: Up to 18°

Communication RS232
Label printer and reports (options)

Type-approval Directive 2014/31/EU
(optional) (Europe)
SE.C. 28.001.A
(Russia)

**Warranty time
two years!**

**The scale may be
used all over the world
and no recalibration
is needed!**

Optional equipment and accessories



Controller with
eSea®System



Rubber feet for secure
mount of the scale



Column mount
and rubber mat

MARINE SCALE

Model				U14512	U14513	U14515	U14516
Platform size (mm)				286x345	350x350	348x415	500x600
Max	Graduation						
3 kg	2kg/2g	3kg/5g		•	-	-	-
10 kg	5kg/5g	10kg/10g		•	-	-	-
15 kg	10kg/10g	15kg/20g		•	-	-	-
30 kg	20kg/20g	30kg/50g		-	•	•	•
70 kg	50kg/50g	70kg/100g		-	•	•	•
150 kg	50kg/50g	100kg/100g	150kg/200g	-	•	•	•

Other platform sizes, capacities and graduations can be provided.

Versions							
230VAC (standard)				•	•	•	•
12-29VDC				•	•	•	•
Internal battery				•	•	•	•
Accessories							
Column mount				-	-	•	•
Rubber mat				•	•	•	•
Rubber feet for secure mount				•	•	•	•
Label printer (print thermal labels, see eSea®Label brochure)				•	•	•	•
Report software (export data for reports to e.g. Excel, see eSea®Indicator brochure)				•	•	•	•
Upgrade to eSea®System (full control and traceability of all catches, see eSea®System brochure)				•	•	•	•
Type of Approval (EU Directive 2014/31/EU or Russian certificate SE.C.28.001.A)				•	•	•	•



UNISYSTEM
SWEDEN
WEIGHING SOLUTIONS

Unisystem AB
Bergebyvägen 24
SE-685 34 TORSBY
Sweden

Phone +46 560 140 55
info@unisystem.se
www.marinescale.com
VAT Reg. No. SE556198973101