

Marine scale

UNI SYSTEM
SWEDEN
WEIGHING SOLUTIONS



www.marinescale.com

FEATURES

| | | | |
|--------------------------|--|--------------------------------------|--|
| Capacities | 3-150 kg | Protection | IP67 |
| Platform sizes | 286x345 mm 350x350 mm 348x415 mm 500x600 mm | Stainless steel | SAE/AISI 304 EN/DIN 1.4301 |
| Measurement speed | 0,4 alt.1,0 Seconds | Compensates automatically for | |
| Powered by | 230VAC (U13702) 12-29VDC (U23712) 12V 7Ah batt. (U23722) | • Gravity: | Worldwide |
| Power consumption | 25mA at 230VAC 200mA at 24VDC | • Motion: | Up to 3 m/s ² |
| Temperature range | -10°C to + 40°C | • Tilt: | Up to 18° |
| | | Communication | RS232 Label printer and reports (options) |
| | | Type-approval (optional) | Directive 2014/31/EU (Europe) SE.C. 28.001.A (Russia) |

**Warranty time
two years!**

**The scale may be
used all over the world
and no recalibration
is needed!**

Optional equipment and accessories



Controller with eSea®System



Rubber feet for secure mount of the scale



Column mount and rubber mat

MARINE SCALE

| Model | | | | U14512 | U14513 | U14515 | U14516 |
|---------------------------|-------------------|------------|------------|---------|---------|---------|---------|
| Platform size (mm) | | | | 286x345 | 350x350 | 348x415 | 500x600 |
| Max | Graduation | | | | | | |
| 3 kg | 2kg/2g | 3kg/5g | | • | - | - | - |
| 10 kg | 5kg/5g | 10kg/10g | | • | - | - | - |
| 15 kg | 10kg/10g | 15kg/20g | | • | - | - | - |
| 30 kg | 20kg/20g | 30kg/50g | | - | • | • | • |
| 70 kg | 50kg/50g | 70kg/100g | | - | • | • | • |
| 150 kg | 50kg/50g | 100kg/100g | 150kg/200g | - | • | • | • |

Other platform sizes, capacities and graduations can be provided.

| Versions | | | | |
|--|---|---|---|---|
| 230VAC (standard) (U13702) | • | • | • | • |
| 12-29VDC (U23712) | • | • | • | • |
| Internal battery (U23722) | • | • | • | • |
| Accessories | | | | |
| Column mount | - | - | • | • |
| Rubber mat | • | • | • | • |
| Rubber feet for secure mount | • | • | • | • |
| Label printer (print thermal labels, see eSea@Label brochure) | • | • | • | • |
| Report software (export data for reports to e.g. Excel, see eSea@Indicator brochure) | • | • | • | • |
| Upgrade to eSea@System (full control and traceability of all catches, see eSea@System brochure) | • | • | • | • |
| Type of Approval (EC Directive 2014/31/EU or Russian certificate SE.C.28.001.A) | • | • | • | • |



UNISYSTEM
SWEDEN
WEIGHING SOLUTIONS

Unisystem AB
Bergebyvägen 24
SE-685 34 TORSBY
Sweden

Phone +46 560 140 55
info@unisystem.se
www.marinescale.com
VAT Reg. No. SE556198973101